

# Safety data sheet

Page: 1/21

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

## A 2A14 SpeedADD 1L

UFI: 1SXM-U51Q-R00Y-P2HQ

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Thinner

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF France SAS  
49, avenue Georges Pompidou  
92593 Levallois-Perret Cedex, FRANCE

Contact address:

BASF plc  
4th and 5th Floors, 2 Stockport Exchange  
Railway Road, Stockport, SK1 3GG  
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-north@basf.com

### 1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

---

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

Skin Corr./Irrit. 2	H315 Causes skin irritation.
Eye Dam./Irrit. 2	H319 Causes serious eye irritation.
Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.
STOT SE 3	H336 May cause drowsiness or dizziness.
STOT RE 2	H373 May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.
Flam. Liq. 3	H226 Flammable liquid and vapour.

For the classifications not written out in full in this section the full text can be found in section 16.

## 2.2. Label elements

### Globally Harmonized System, EU (GHS)

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection or face protection.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
-------------	--

Precautionary Statements (Disposal):

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

P501 Dispose of contents and container to hazardous or special waste collection point.

Hazard determining component(s) for labelling: heptan-2-one, n-butyl acetate, xylene, Solvent naphtha (petroleum), light arom.

### 2.3. Other hazards

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

---

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

#### Chemical nature

organic solvent

#### Hazardous ingredients (GHS)

n-butyl acetate

Content (W/W): $\geq 50\%$ - $< 75\%$	Flam. Liq. 3
CAS Number: 123-86-4	STOT SE 3 (drowsiness and dizziness)
EC-Number: 204-658-1	H226, H336
REACH registration number: 01-2119485493-29	EUH066
INDEX-Number: 607-025-00-1	

xylene

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

<p>Content (W/W): <math>\geq 12.5\%</math> - <math>&lt; 15\%</math>  CAS Number: 1330-20-7  EC-Number: 215-535-7  REACH registration number: 01-2119488216-32  INDEX-Number: 601-022-00-9</p>	<p>Asp. Tox. 1  Flam. Liq. 3  Acute Tox. 4 (Inhalation - vapour)  Acute Tox. 4 (dermal)  Skin Corr./Irrit. 2  Eye Dam./Irrit. 2  STOT SE 3 (irr. to respiratory syst.)  STOT RE (Central nervous system, Liver, Kidney) 2  Aquatic Chronic 3  H226, H319, H315, H312, H332, H304, H335, H373, H412</p>
---	--

## | heptan-2-one

<p>Content (W/W): <math>\geq 10\%</math> - <math>&lt; 12.5\%</math>  CAS Number: 110-43-0  EC-Number: 203-767-1  REACH registration number: 01-2119902391-49  INDEX-Number: 606-024-00-3</p>	<p>Flam. Liq. 3  Acute Tox. 4 (Inhalation - vapour)  Acute Tox. 4 (oral)  STOT SE 3 (drowsiness and dizziness)  H226, H336, H302 + H332</p>
--	---

## ethylbenzene

<p>Content (W/W): <math>\geq 2.5\%</math> - <math>&lt; 3\%</math>  CAS Number: 100-41-4  EC-Number: 202-849-4  REACH registration number: 01-2119489370-35  INDEX-Number: 601-023-00-4</p>	<p>Asp. Tox. 1  Flam. Liq. 2  Acute Tox. 4 (Inhalation - vapour)  STOT RE (Auditory organ) 2  Aquatic Chronic 3  H225, H332, H304, H373, H412</p>
--	---

## Solvent naphtha (petroleum), light arom.

<p>Content (W/W): <math>\geq 2\%</math> - <math>&lt; 2.5\%</math>  CAS Number: 64742-95-6  EC-Number: 265-199-0  REACH registration number: 01-2119455851-35, 01-2119486773-24  INDEX-Number: 649-356-00-4</p>	<p>Asp. Tox. 1  Flam. Liq. 3  Skin Corr./Irrit. 2  STOT SE 3 (drowsiness and dizziness)  Aquatic Chronic 2  H226, H315, H304, H336, H411  EUH066</p>
--	--

## 1,2,4-trimethylbenzene

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

Content (W/W):  $\geq 1\%$  -  $< 2\%$

CAS Number: 95-63-6

EC-Number: 202-436-9

INDEX-Number: 601-043-00-3

Asp. Tox. 1

Flam. Liq. 3

Acute Tox. 4 (Inhalation - vapour)

Skin Corr./Irrit. 2

Eye Dam./Irrit. 2

Aquatic Chronic 2

STOT SE 3 (irr. to respiratory syst.)

H226, H319, H315, H332, H304, H335, H411

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

---

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Eye irritation, aspiration pneumonia, dazed state, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

---

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

---

### **SECTION 5: Fire-Fighting Measures**

#### **5.1. Extinguishing media**

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

#### **5.2. Special hazards arising from the substance or mixture**

Advice: Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

#### **5.3. Advice for fire-fighters**

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

---

### **SECTION 6: Accidental Release Measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

#### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

#### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

#### **6.4. Reference to other sections**

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

---

## SECTION 7: Handling and Storage

### 7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

### 7.3. Specific end use(s)

Please refer to the technical leaflet for further information.

---

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

Components with occupational exposure limits

95-63-6: 1,2,4-trimethylbenzene

TWA value 125 mg/m<sup>3</sup> ; 25 ppm (WEL/EH 40 (UK))

TWA value 100 mg/m<sup>3</sup> ; 20 ppm (OEL (EU))

indicative

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

100-41-4: ethylbenzene

Skin Designation (WEL/EH 40 (UK))

The substance can be absorbed through the skin.

TWA value 441 mg/m<sup>3</sup> ; 100 ppm (WEL/EH 40 (UK))

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

STEL value 884 mg/m<sup>3</sup> ; 200 ppm (OEL (EU))

indicative

TWA value 442 mg/m<sup>3</sup> ; 100 ppm (OEL (EU))

indicative

STEL value 552 mg/m<sup>3</sup> ; 125 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

110-43-0: heptan-2-one

Skin Designation (WEL/EH 40 (UK))

The substance can be absorbed through the skin.

TWA value 237 mg/m<sup>3</sup> ; 50 ppm (WEL/EH 40 (UK))

TWA value 238 mg/m<sup>3</sup> ; 50 ppm (OEL (EU))

indicative

STEL value 475 mg/m<sup>3</sup> ; 100 ppm (OEL (EU))

indicative

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

STEL value 475 mg/m<sup>3</sup> ; 100 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

123-86-4: n-butyl acetate

TWA value 724 mg/m<sup>3</sup> ; 150 ppm (WEL/EH 40 (UK))

STEL value 723 mg/m<sup>3</sup> ; 150 ppm (OEL (EU))

indicative

TWA value 241 mg/m<sup>3</sup> ; 50 ppm (OEL (EU))

indicative

STEL value 966 mg/m<sup>3</sup> ; 200 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

1330-20-7: xylene

TWA value 220 mg/m<sup>3</sup> ; 50 ppm (WEL/EH 40 (UK))

Skin Designation (WEL/EH 40 (UK))

The substance can be absorbed through the skin.

STEL value 442 mg/m<sup>3</sup> ; 100 ppm (OEL (EU))

indicative

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

TWA value 221 mg/m<sup>3</sup> ; 50 ppm (OEL (EU))

indicative

STEL value 441 mg/m<sup>3</sup> ; 100 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

Components with biological limit values

1330-20-7: xylene

UKEH40BMGV



BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

Determinant: methylhippuric (toluric) acid

Biological Specimen: Creatinine in urine

Sampling time: End of shift

Concentration: 650 mmol/mol

#### Components with PNEC

##### 100-41-4: ethylbenzene

freshwater: 0.1 mg/l

marine water: 0.01 mg/l

intermittent release: 0.1 mg/l

sediment (freshwater): 13.7 mg/kg

soil: 2.68 mg/kg

STP: 9.6 mg/l

oral (secondary poisoning): 0.02 mg/kg

##### 110-43-0: heptan-2-one

freshwater: 0.0982 mg/l

marine water: 0.00982 mg/l

intermittent release: 0.982 mg/l

STP: 12.5 mg/l

sediment (freshwater): 1.89 mg/kg

sediment (marine water): 0.189 mg/kg

soil: 0.321 mg/kg

##### 123-86-4: n-butyl acetate

freshwater: 0.18 mg/l

marine water: 0.018 mg/l

intermittent release: 0.36 mg/l

STP: 35.6 mg/l

sediment (freshwater): 0.981 mg/kg

sediment (marine water): 0.0981 mg/kg

soil: 0.0903 mg/kg

##### 1330-20-7: xylene

freshwater: 0.327 mg/l

marine water: 0.327 mg/l

intermittent release: 0.327 mg/l

STP: 6.58 mg/l

sediment (freshwater): 12.46 mg/kg

sediment (marine water): 12.46 mg/kg

soil: 2.31 mg/kg

oral (secondary poisoning):

No PNEC oral derived, as accumulation in organisms is not to be expected.

#### Components with DNEL

##### 100-41-4: ethylbenzene

worker: Short-term exposure - local effects, Inhalation: 293 mg/m<sup>3</sup>

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

worker: Long-term exposure- systemic effects, Inhalation: 77 mg/m<sup>3</sup>, 17.73 ppm  
 worker: Long-term exposure- systemic effects, dermal: 180 mg/kg  
 consumer: Long-term exposure- systemic effects, Inhalation: 15 mg/m<sup>3</sup>  
 consumer: Long-term exposure- systemic effects, oral: 1.6 mg/kg

110-43-0: heptan-2-one

worker: Long-term exposure- systemic effects, dermal: 54.27 mg/kg  
 worker: Long-term exposure- systemic effects, Inhalation: 394.25 mg/m<sup>3</sup>  
 worker: Short-term exposure - systemic effects, Inhalation: 1516 mg/m<sup>3</sup>  
 consumer: Long-term exposure- systemic effects, dermal: 23.32 mg/kg  
 consumer: Long-term exposure- systemic effects, Inhalation: 84.31 mg/m<sup>3</sup>  
 consumer: Long-term exposure- systemic effects, oral: 23.32 mg/kg

123-86-4: n-butyl acetate

worker: Short-term exposure - local effects, Inhalation: 600 mg/m<sup>3</sup>  
 worker: Long-term exposure - local effects, Inhalation: 300 mg/m<sup>3</sup>  
 consumer: Short-term exposure - local effects, Inhalation: 300 mg/m<sup>3</sup>  
 consumer: Long-term exposure - local effects, Inhalation: 35.7 mg/m<sup>3</sup>  
 worker: Long-term exposure- systemic effects, dermal: 11 mg/kg  
 worker: Short-term exposure - systemic effects, dermal: 11 mg/kg  
 consumer: Long-term exposure- systemic effects, dermal: 6 mg/kg  
 consumer: Short-term exposure - systemic effects, dermal: 6 mg/kg  
 consumer: Long-term exposure- systemic effects, oral: 2 mg/kg  
 consumer: Short-term exposure - systemic effects, oral: 2 mg/kg

1330-20-7: xylene

worker: Long-term exposure- systemic effects, Inhalation: 77 mg/m<sup>3</sup>  
 worker: Short-term exposure - systemic effects, Inhalation: 289 mg/m<sup>3</sup>  
 worker: Long-term exposure- systemic effects, dermal: 180 mg/kg  
 consumer: Long-term exposure- systemic effects, Inhalation: 14.8 mg/m<sup>3</sup>  
 consumer: Short-term exposure - systemic effects, Inhalation: 174 mg/m<sup>3</sup>  
 consumer: Long-term exposure- systemic effects, dermal: 108 mg/kg  
 consumer: Long-term exposure- systemic effects, oral: 1.6 mg/kg

64742-95-6: Solvent naphtha (petroleum), light arom.

worker: Short-term exposure - systemic effects, Inhalation: 1286.4 mg/m<sup>3</sup>  
 worker: Long-term exposure - local effects, Inhalation: 837.5 mg/m<sup>3</sup>  
 worker: Short-term exposure - local effects, Inhalation: 1066.67 mg/m<sup>3</sup>  
 consumer: Short-term exposure - systemic effects, Inhalation: 1152 mg/m<sup>3</sup>  
 consumer: Long-term exposure - local effects, Inhalation: 178.57 mg/m<sup>3</sup>  
 consumer: Short-term exposure - local effects, Inhalation: 640 mg/m<sup>3</sup>

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

---

### Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:

Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties). Follow manufacturer's advice on use, storage, maintenance and replacement of gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,7 mm

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166), Required when there is a risk of eye contact.

Body protection:

Anti-static protective clothing, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

### General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

### Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

---

## **SECTION 9: Physical and Chemical Properties**

### **9.1. Information on basic physical and chemical properties**

Form:	liquid
Colour:	colourless
Odour:	ester-like
pH value:	substance/mixture is non-polar/aprotic

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

Melting point:	not determined	
onset of boiling:	114.00 °C	
Flash point:	24 °C	(ISO 3679)
Flammability:	Flammable liquid and vapour.	
Lower explosion limit:	36 g/m <sup>3</sup>	
Ignition temperature:	> 200.00 °C	
Vapour pressure:	12.00 hPa (20 °C)	(calculated)
	(50 °C)	
	not determined	
Density:	0.867 g/cm <sup>3</sup> (20 °C)	
Viscosity, kinematic:	6.0 mm <sup>2</sup> /s (20 °C)	
	(40 °C)	
	not determined	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

## 9.2. Other information

Burning rate:	The material doesn't meet the criteria specified in paragraph 33.2.4.4 of UN manual of tests and criteria.	(UN Test N.1 (ready combustible solids))
Self heating ability:	It is not a substance capable of spontaneous heating.	
Miscibility with water:	immiscible	
Flow time:	< 30 s	(DIN EN ISO 2431; 3 mm)

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### 10.3. Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

### 10.4. Conditions to avoid

Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

### 10.5. Incompatible materials

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

### 10.6. Hazardous decomposition products

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

---

## SECTION 11: Toxicological Information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Assessment of acute toxicity:

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The mixture has been assessed following regulation (EC) No 1272/2008. See sections 2 and 3 for details.

Based on available data, the classification criteria are not met.

*Information on: ethylbenzene*

*Experimental/calculated data:*

*LD50 rat (oral): 3,500 mg/kg*

*Literature data.*

*Information on: heptan-2-one*

*Experimental/calculated data:*

*LD50 rat (oral): approx. 1,600 mg/kg*

*Information on: xylene*

*Experimental/calculated data:*

*LD50 rat (oral): 3,523 mg/kg (similar to OECD guideline 401)*

-----

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

*Information on: 1,2,4-trimethylbenzene*

*Experimental/calculated data:*

*LC50 rat (by inhalation): > 10.2 mg/l 4 h (other)*

*The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The vapour was tested.*

*Information on: heptan-2-one*

*Experimental/calculated data:*

*LC50 rat (by inhalation): > 16.7 mg/l 4 h (OECD Guideline 403)*

*Mortality was observed. The vapour was tested.*

*Information on: ethylbenzene*

*Experimental/calculated data:*

*LD50 rabbit (dermal): 15,354 mg/kg*

*Literature data.*

#### Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Eye contact causes irritation. Skin contact causes irritation.

#### Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

#### Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

---

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated exposure may affect certain organs.

#### Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

#### Interactive effects

No data available.

### **11.2. Information on other hazards**

---

## **SECTION 12: Ecological Information**

### **12.1. Toxicity**

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is classified for ecotoxicological properties accordingly. See sections 2 and 3 for details.

### **12.2. Persistence and degradability**

Assessment biodegradation and elimination (H<sub>2</sub>O):

Biological degradability of hazardous substances mentioned in section 3:

*Information on: 1,2,4-trimethylbenzene*

*Elimination information:*

*> 20 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic)*

*The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: ethylbenzene*

*Elimination information:*

*70 - 80 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge) Readily biodegradable (according to OECD criteria).*

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

---

*Information on: xylene*

*Elimination information:*

*87.8 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)*

*The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Elimination information:*

*77 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic, non-adapted)*

*96 % CO<sub>2</sub> formation relative to the theoretical value (28 d) (ISO 14593) (aerobic, activated sludge, domestic, adapted)*

-----

### **12.3. Bioaccumulative potential**

Bioaccumulation potential:

No data available.

### **12.4. Mobility in soil**

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

### **12.5. Results of PBT and vPvB assessment**

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

### **12.6. Endocrine disrupting properties**

### **12.7. Other adverse effects**

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

---

## **SECTION 13: Disposal Considerations**

### **13.1. Waste treatment methods**

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Dispose of the substance/product as special waste in accordance with Directive 2008/98/EC.



---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

---

Waste key:

08 01 11<sup>□</sup> waste paint and varnish containing organic solvents or other hazardous substances

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

---

## SECTION 14: Transport Information

### Land transport

ADR

UN number or ID number: UN1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Special precautions for user: None known

### Inland waterway transport

ADN

UN number or ID number: UN1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Special precautions for user: None known

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

#### Transport in inland waterway vessel

Not evaluated

#### **Sea transport**

##### IMDG

UN number or ID number: UN 1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3

Packing group: III

Environmental hazards: no

Marine pollutant: NO

Special precautions for user: EmS: F-E; S-E

#### **Air transport**

##### IATA/ICAO

UN number or ID number: UN 1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3

Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for user: None known

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

---

#### **14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Maritime transport in bulk is not intended.

---

### **SECTION 15: Regulatory Information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

VOC content: 99.1 % organic solvents

VOC content: 99.1 % calculated

VOC content: 870.0 g/l

#### Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 20, 3, 40, 75, 48

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):  
Listed in above regulation: Flammable liquids, Categories 2 or 3 not covered by P5a and P5b

Details relating to the VOC Directive 2004/42/EC:

Subcategory as indicated in Annex IIB:

dropped

Limit value for maximum VOC content as specified in Annex IIB:

dropped

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

#### **15.2. Chemical Safety Assessment**

Chemical Safety Assessment not required

---

### **SECTION 16: Other Information**

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Asp. Tox.	Aspiration hazard
STOT SE	Specific target organ toxicity — single exposure
STOT RE	Specific target organ toxicity — repeated exposure
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Flam. Liq.	Flammable liquids
Acute Tox.	Acute toxicity
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure.
H302 + H332	Harmful if swallowed or if inhaled
H225	Highly flammable liquid and vapour.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the

---

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 14.06.2022

Version: 7.0

Date previous version: 20.03.2022

Previous version: 6.7

Date / First version: 26.10.2020

Product: **A 2A14 SpeedADD 1L**

(ID no. 50685414/SDS\_GEN\_GB/EN)

Date of print 15.06.2022

---

corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

---

Vertical lines in the left hand margin indicate an amendment from the previous version.