

ONYX ACTIVATOR

A 2210

Waterborne basecoat activator

Application:

- For special applications recommended by car manufactures, the usage of ONYX ACTIVATOR could be necessary in ONYX HD basecoats.
- Additive for solid-colour ONYX HD and for use in solid-color basecoats applied as a ground coat in ONYX HD 3-layer systems to improve tape resistance and hardness.

Solid Content	78 %
Density	1.03-1.13 g/cm ³
Storage temperature	5-45 °C
Shelf life	24 months

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

