

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Bulldog Export Filler  
Product code : 153.286

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Body filler/stopper  
Recommended restrictions : Industrial use, professional use  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH  
Esinger Steinweg 50  
25436 Uetersen  
Germany  
info@vosschemie.de

Telephone : 04122 717 0  
Telefax : 04122 717158

**Organisation that prepared  
the SDS** : Laboratory  
04122 717 0  
sds@vosschemie.de

#### 1.4 Emergency telephone number

Telephone : Giftinformationszentrum (GIZ)-Nord,  
Göttingen, Deutschland  
0551 19240

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version DE / EN Revision Date: Date of last issue: 12.11.2024  
4.2 10.03.2026 Date of first issue: 28.06.2022

---

### SECTION 2: Hazards identification


#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H361d Suspected of damaging the unborn child. H372 Causes damage to organs through prolonged or repeated exposure.
Precautionary statements	:	<b>Prevention:</b> P201 Obtain special instructions before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe dust / mist / vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  <b>Response:</b> P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Bulldog Export Filler

Version DE / EN Revision Date: Date of last issue: 12.11.2024  
4.2 10.03.2026 Date of first issue: 28.06.2022

attention.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

### Hazardous components which must be listed on the label:

styrene  
maleic anhydride

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Formulated product  
contains

Resin

### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3;	>= 10 - < 20

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version  
4.2

DE / EN

Revision Date:  
10.03.2026

Date of last issue: 12.11.2024  
Date of first issue: 28.06.2022

		H412 Acute toxicity estimate Acute inhalation toxicity (vapour): 11,8 mg/l	
unsaturated polyester polymer	Not Assigned	Aquatic Chronic 4; H413 Acute toxicity estimate Acute oral toxicity: > 2.000 mg/kg Acute inhalation toxicity (dust/mist): > 5 mg/l Acute dermal toxicity: > 2.000 mg/kg	>= 2,5 - < 10
maleic anhydride	108-31-6 203-571-6 607-096-00-9 01-2119472428-31	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system) EUH071  specific concentration limit Skin Sens. 1A; H317 >= 0,001 %  Acute toxicity estimate  Acute oral toxicity: 1.090 mg/kg	>= 0,001 - < 0,1
Substances with a workplace exposure limit :			
Talc	14807-96-6 238-877-9		>= 30 - < 50

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
Move out of dangerous area.  
Take off contaminated clothing and shoes immediately.  
Do not leave the victim unattended.  
Symptoms of poisoning may appear several hours later.  
Show this safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
If easy to do, remove contact lens, if worn.  
Consult a physician.
- If swallowed : Rinse mouth with water.  
Do NOT induce vomiting.  
Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspected of damaging the unborn child.  
Causes damage to organs through prolonged or repeated exposure.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.  
Keep under medical supervision for at least 48 hours.
- 

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

Dry powder  
Water spray jet  
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Do not smoke.  
Avoid contact with skin, eyes and clothing.  
Sweep up to prevent slipping hazard.  
In the case of vapour formation use a respirator with an approved filter.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.



# SAFETY DATA SHEET

VOSSCHEMIE

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Bulldog Export Filler

Version DE / EN  
4.2

Revision Date:  
10.03.2026

Date of last issue: 12.11.2024  
Date of first issue: 28.06.2022

		tolerance values, there is no risk of harming the unborn child		
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		TWA (Respirable dust)	0,1 mg/m <sup>3</sup>	2004/37/EC
		Further information: Carcinogens or mutagens		
		BM (Alveolar dust fraction)	0,5 mg/m <sup>3</sup>	DE TRGS 527
styrene	100-42-5	AGW	20 ppm 86 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		MAK	20 ppm 86 mg/m <sup>3</sup>	DE DFG MAK
		Peak-limit: excursion factor (category): 2; II		
		Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed		
Barium sulphate	7727-43-7	MAK (measured as the alveolate fraction)	0,3 mg/m <sup>3</sup>	DE DFG MAK
		Peak-limit: excursion factor (category): 8; II		
		Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed		
		MAK (inhalable fraction)	4 mg/m <sup>3</sup>	DE DFG MAK
		Peak-limit: excursion factor (category): 8; II		
		Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed		
		AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
		BM (Alveolar dust fraction)	0,5 mg/m <sup>3</sup>	DE TRGS 527
Titanium dioxide	13463-67-7	AGW (Inhalable)	10 mg/m <sup>3</sup>	DE TRGS

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Bulldog Export Filler

Version 4.2 DE / EN

Revision Date: 10.03.2026

Date of last issue: 12.11.2024  
Date of first issue: 28.06.2022

		fraction)	(Titanium dioxide)	900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium dioxide)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m3	DE TRGS 527
		MAK (measured as the alveolate fraction)	0,3 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 8; II			
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
maleic anhydride	108-31-6	AGW (Vapour and aerosols)	0,02 ppm 0,081 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 1; =2.5=(I)			
	Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system			
		Mow	0,05 ppm 0,2 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 1; I			
	Further information: Danger of sensitization of the airways and the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		MAK	0,02 ppm 0,081 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 1; I			
	Further information: Danger of sensitization of the airways and the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
styrene	100-42-5	mandelic acid + phenylglyoxylic acid: 600 mg/g creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903
		mandelic acid plus phenylglyoxylic acid: 600 mg/g creatinine (Urine)	Immediately after exposition or after working hours	DE DFG BAT

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version DE / EN  
4.2

Revision Date:  
10.03.2026

Date of last issue: 12.11.2024  
Date of first issue: 28.06.2022

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
styrene	Workers	Dermal	Long-term systemic effects, Chronic effects	406 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects, Chronic effects	85 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects, Chronic effects	289 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects, Short-term exposure	306 mg/m <sup>3</sup>
	Consumers	Oral	Long-term systemic effects, Chronic effects	2,1 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects, Chronic effects	343 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Chronic effects	10,2 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects, Short-term exposure	174,25 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects, Short-term exposure	182,75 mg/m <sup>3</sup>
maleic anhydride	Workers	Inhalation	Long-term systemic effects	0,081 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	0,2 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
styrene	Fresh water	0,028 mg/l
	Marine water	0,014 mg/l
	Fresh water sediment	0,614 mg/kg dry weight (d.w.)
	Marine sediment	0,307 mg/kg dry weight (d.w.)
	Soil	0,2 mg/kg dry weight (d.w.)
	Sewage treatment plant	5 mg/l
maleic anhydride	Fresh water	0,038 mg/l
	Marine water	0,004 mg/l
	Fresh water sediment	0,296 mg/kg dry weight (d.w.)
	Marine sediment	0,03 mg/kg dry weight (d.w.)
	Soil	0,037 mg/kg dry weight (d.w.)
	Sewage treatment plant	44,6 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

### 8.2 Exposure controls

#### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Safety glasses with side-shields conforming to EN166

#### Hand protection

Guideline : Equipment should conform to EN 374

Material : PVA  
Break through time : > 480 min  
Glove thickness : 0,2 - 0,3 mm

Material : Fluorinated rubber  
Break through time : > 480 min  
Glove thickness : >= 0,4 mm

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection  
Avoid neoprene and natural rubber gloves.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing  
Equipment should conform to EN 13688

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.  
Dry sanding, flame cutting and/or welding of the cured material will give rise to dust and/or hazardous fumes.  
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Combined particulates and organic vapour type (A-P)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
Avoid contact with the skin and the eyes.  
Use only with adequate ventilation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version      DE / EN      Revision Date:      Date of last issue: 12.11.2024  
4.2                              10.03.2026      Date of first issue: 28.06.2022

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Form	:	paste
Colour	:	beige
Odour	:	characteristic
Melting point/ range	:	-30 °C Literary value styrene
Boiling point/boiling range	:	145 °C (1.013 hPa) Literary value styrene
Flammability	:	Flammable
Upper explosion limit / Upper flammability limit	:	6,1 %(V) Literary value styrene
Lower explosion limit / Lower flammability limit	:	1,1 %(V) Literary value styrene
Flash point	:	31 °C(1.013 hPa) Literary value styrene
Auto-ignition temperature	:	490 °C (1.013 hPa) Literary value styrene
Decomposition temperature	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Solubility(ies)		

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

Water solubility	:	0,32 g/l (25 °C) Literary value styrene
Partition coefficient: n-octanol/water	:	log Pow: 2,96 (25 °C) Literary value styrene
Vapour pressure	:	6,67 hPa (20 °C) Literary value styrene
Density	:	ca. 1,4 g/cm <sup>3</sup> (20 °C)
Relative vapour density	:	No data available

### 9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapour-air mixture.
------------	---	---

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Avoid radical-forming starting agents, peroxides and reactive metals. Polymerisation can occur. Polymerisation is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.
---------------------	---	--

### 10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks. Strong sunlight for prolonged periods.
---------------------	---	--

### 10.5 Incompatible materials

Materials to avoid	:	Strong acids and oxidizing agents polymerisation initiators Copper Copper alloys Brass
--------------------	---	--

### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

##### Components:

###### **styrene:**

Acute oral toxicity : LD50 Oral (Rat): 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11,8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402

###### **unsaturated polyester polymer:**

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

###### **maleic anhydride:**

Acute oral toxicity : LD50 Oral (Rat): 1.090 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 4,35 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): 2.620 mg/kg

###### **Talc:**

Acute oral toxicity : LD50 Oral (Rat): 5.000 mg/kg  
Method: OECD Test Guideline 423

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

VOSSCHEMIE

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402

### Skin corrosion/irritation

Causes skin irritation.

#### Components:

##### styrene:

Species : Rabbit  
Result : irritating

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Components:

##### styrene:

Species : Rabbit  
Result : irritating

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Components:

##### styrene:

Species : Guinea pig  
Result : Does not cause skin sensitisation.

##### maleic anhydride:

Result : The product is a skin sensitiser, sub-category 1A.

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Suspected of damaging the unborn child.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version DE / EN  
4.2

Revision Date:  
10.03.2026

Date of last issue: 12.11.2024  
Date of first issue: 28.06.2022

---

### Components:

#### **styrene:**

Reproductive toxicity - Assessment : Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

#### **STOT - single exposure**

Not classified due to lack of data.

### Components:

#### **styrene:**

Assessment : May cause respiratory irritation.

#### **STOT - repeated exposure**

Causes damage to organs (hearing organs) through prolonged or repeated exposure if inhaled.

### Components:

#### **styrene:**

Exposure routes : Inhalation  
Target Organs : hearing organs  
Assessment : Causes damage to organs through prolonged or repeated exposure.

#### **maleic anhydride:**

Exposure routes : Inhalation  
Target Organs : Respiratory system  
Assessment : Causes damage to organs through prolonged or repeated exposure.

#### **Aspiration hazard**

Not classified due to lack of data.

### Components:

#### **styrene:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

#### **Endocrine disrupting properties**

Not classified due to lack of data.

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version      DE / EN      Revision Date:      Date of last issue: 12.11.2024  
4.2                              10.03.2026      Date of first issue: 28.06.2022

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **styrene:**

- Toxicity to fish                              : LC50 (Pimephales promelas (fathead minnow)): 4,02 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other              : EC50 (Daphnia magna (Water flea)): 4,7 mg/l  
aquatic invertebrates                      Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic                    : EC50 (Selenastrum capricornutum (green algae)): 4,9 mg/l  
plants    Exposure time: 72 h
- EC10 (Selenastrum capricornutum (green algae)): 0,28 mg/l  
Exposure time: 96 h
- Toxicity to microorganisms                : EC50 (Natural microorganism): ca. 500 mg/l  
Method: OECD Test Guideline 209
- Toxicity to daphnia and other              : NOEC: 1,01 mg/l  
aquatic invertebrates (Chronic              Exposure time: 21 d  
toxicity)    Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

##### **Ecotoxicology Assessment**

- Chronic aquatic toxicity                    : Harmful to aquatic life with long lasting effects.

##### **unsaturated polyester polymer:**

##### **Ecotoxicology Assessment**

- Chronic aquatic toxicity                    : May cause long lasting harmful effects to aquatic life.

##### **maleic anhydride:**

- Toxicity to fish                              : LC50 (Lepomis macrochirus (Bluegill sunfish)): 75 mg/l  
Exposure time: 96 h  
Method: EPA-660/3-75-00
- Toxicity to daphnia and other              : EC50 (Daphnia magna (Water flea)): 37,9 mg/l  
aquatic invertebrates                      Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic                    : EC50 (Pseudokirchneriella subcapitata (green algae)): 65,78  
plants    mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### 12.2 Persistence and degradability

#### Components:

##### **styrene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70,9 %  
Exposure time: 28 d

##### **maleic anhydride:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 90 %  
Exposure time: 225 d  
Method: OECD Test Guideline 301B

### 12.3 Bioaccumulative potential

#### Components:

##### **styrene:**

Partition coefficient: n-octanol/water : log Pow: 2,96 (25 °C)

##### **maleic anhydride:**

Partition coefficient: n-octanol/water : log Pow: -2,61 (20 °C)

##### **Talc:**

Partition coefficient: n-octanol/water : log Pow: -9,4 (25 °C)  
pH: 7

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Dispose of in accordance with local regulations.  
Dispose of wastes in an approved waste disposal facility.  
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Store containers and offer for recycling of material when in accordance with the local regulations.  
Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:  
07 02 08, other still bottoms and reaction residues

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN	:	UN 1866
ADR	:	UN 1866
RID	:	UN 1866
IMDG	:	UN 1866
IATA	:	UN 1866

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Bulldog Export Filler

Version      DE / EN      Revision Date:      Date of last issue: 12.11.2024  
4.2                              10.03.2026      Date of first issue: 28.06.2022

---

### 14.2 UN proper shipping name

**ADN**                              : RESIN SOLUTION  
**ADR**                              : RESIN SOLUTION  
**RID**                              : RESIN SOLUTION  
**IMDG**                             : RESIN SOLUTION  
**IATA**                             : Resin solution

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

**ADN**  
Packing group                    : III  
Classification Code             : F1  
Hazard Identification Number   : 30  
Labels                             : 3

**ADR**  
Packing group                    : III  
Classification Code             : F1  
Hazard Identification Number   : 30  
Labels                             : 3  
Tunnel restriction code         : (D/E)

**RID**  
Packing group                    : III  
Classification Code             : F1  
Hazard Identification Number   : 30  
Labels                             : 3

**IMDG**  
Packing group                    : III  
Labels                             : 3  
EmS Code                         : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo     : 366  
aircraft)  
Packing instruction (LQ)       : Y344  
Packing group                    : III  
Labels                             : Flammable Liquids

**IATA (Passenger)**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

**VOSSCHEMIE**

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 40  
This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.

Number on list 75  
If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EU) No 2024/590 on substances that de- : Not applicable

# SAFETY DATA SHEET

VOSSCHEMIE

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

---

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: < 250 g/l  
VOC content for the product in a ready to use condition.

### Other regulations:

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

---

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# SAFETY DATA SHEET

VOSSCHEMIE

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

H335 : May cause respiratory irritation.  
H361d : Suspected of damaging the unborn child.  
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.  
H372 : Causes damage to organs through prolonged or repeated exposure.  
H412 : Harmful to aquatic life with long lasting effects.  
H413 : May cause long lasting harmful effects to aquatic life.  
EUH071 : Corrosive to the respiratory tract.  
H317 : May cause an allergic skin reaction.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Repr. : Reproductive toxicity  
Resp. Sens. : Respiratory sensitisation  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
Skin Sens. : Skin sensitisation  
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work - Annex III  
DE DFG BAT : Germany. MAK BAT Annex XIII  
DE DFG MAK : Germany. MAK BAT Annex IIa  
DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 903 : c - Biological limit values  
2004/37/EC / TWA : Long term exposure limit  
DE DFG MAK / Mow : Momentary value  
DE DFG MAK / MAK : MAK value  
DE TRGS 527 / BM : Assessment scale  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - Interna-

# SAFETY DATA SHEET

VOSSCHEMIE

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## Bulldog Export Filler

Version	DE / EN	Revision Date:	Date of last issue: 12.11.2024
4.2		10.03.2026	Date of first issue: 28.06.2022

tional Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 2	H361d
STOT RE 1	H372

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN